



# Product Specification

Domestic Range

C

## 400 L Direct Solar

Capacity	Type	Model	Installation
400L	Unvented	Direct Solar	Floor Standing

### Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 102 W

### Constructive Specifications

Capacity	400L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	71
Weight (full) kg	471
Max. Operating Pressure (bar)	5
Test Pressure (bar)	10
Max. Working Temperature (c)	90
Heating Elements	2 No. Incoloy Immersion
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Heat Loss (W)	102
Heat up Time (mins)	48
Solar Coil Surface Area (m <sup>2</sup> )	1.15
Solar Coil kW Rating	30
Product Code	TCIMVE-0400LFC
Energy Efficiency Class	C

### Dimensions

A	1570
B	710
C	225
D	275
E	430
F	615
G	680
H	915
I	1190
J	1290

