



Product Specification

Domestic Range

C

200 L Horizontal Indirect

| Capacity | Type | Model | Installation |
|----------|----------|---------------------|------------------|
| 200L | Unvented | Horizontal Indirect | Floor Horizontal |

Descriptive Specification

- The unit is to be horizontally positioned Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 81 W

| Constructive Specifications | |
|-------------------------------|---|
| Capacity | 200 L |
| Cylinder Material | Stainless Steel Duplex LDX 2101 |
| Thermal Insulation | Polyurethane foam CFC-Free and HCFC Free |
| Casing | Painted Galvanised Carbon Steel DX51D |
| Coil Material | Stainless Steel Tube AISI 316L |
| Weight (empty) kg | 46 |
| Weight (full) kg | 243 |
| Max. Operating Pressure (bar) | 5 |
| Test Pressure (bar) | 10 |
| Max. Working Temperature (c) | 95 |
| Heating Elements | 1 No. Incoloy Immersion |
| Unvented Kit Components | Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish |
| Heat Loss (W) | 81 |
| Heat up Time (mins) | 31 |
| Product Code | TCIMHI-0200NFC |
| Energy Efficiency % | 35 |
| Energy Efficiency Class | C |

| Dimensions | |
|------------|------|
| Length | 1450 |
| Diameter | 530 |

Indirect

