



Product Specification

Domestic Range

C

200 L Pre-plumbed Indirect

| Capacity | Type | Model | Installation |
|----------|----------|----------------------|----------------|
| 200L | Unvented | Pre-plumbed Indirect | Floor Standing |

Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 78 W

Constructive Specifications

| | |
|--------------------------------|--|
| Capacity | 200L |
| Cylinder Material | Stainless Steel Duplex LDX 2101 |
| Thermal Insulation | Polyurethane foam CFC-Free and HCFC Free |
| Casing | Painted Galvanised Carbon Steel DX51D |
| Coil Material | Stainless Steel Tube AISI 316L |
| Weight (empty) kg | 59 |
| Weight (full) kg | 256 |
| Max. Operating Pressure (bar) | 5 |
| Test Pressure (bar) | 10 |
| Max. Working Temperature (c) | 90 |
| Boiler Coil Rating (kW) | 16 |
| Heating Elements | 1. No. Incoloy Immersion |
| Heat Loss (W) | 78 |
| Heat up Time (mins) | 21 |
| Product Code: Heat Only/System | TUMI-H0200-L3B/TUMI-S0200-L3B |
| Energy Efficiency Class | C |

Dimensions

| | |
|---|------|
| A | 1085 |
| B | 560 |
| C | 196 |
| D | 316 |
| E | 416 |
| F | 410 |
| G | 763 |
| H | 991 |
| I | 1400 |
| J | 1440 |
| X | 570 |
| Y | 680 |

