



Product Specification

Domestic Range

C

400 L High Gain Solar

Capacity	Type	Model	Installation
400L	Unvented	High Gain Solar	Floor Standing

Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 105 W

Constructive Specifications

Capacity	400 L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	84
Weight (full) kg	486
Max. Operating Pressure (bar)	5
Test Pressure (bar)	10
Max. Working Temperature (c)	95
Heating Elements	1 No. Incoloy Immersion
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Heat Loss (W)	105
Heat up Time (mins)	42
Solar Coil Surface Area (m ²)	0.77
Solar Coil Rating (kW)	22
High Gain Coil Surface Area (m ²)	3.5
Product Code	TCIMVG-0400NFC
Energy Efficiency Class	C

Dimensions

A	1570
B	710
C	225
D	275
E	375
F	415
G	465
H	515
I	950
J	1190
K	1285
L	1290

