



Product Specification

Domestic Range

C

400L Twin Solar

Capacity	Type	Model	Installation
400L	Unvented	Twin Solar	Floor Standing

Descriptive Specification


- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing heat loss of no more than 102 W

Constructive Specifications

Capacity	400L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	74
Weight (full) kg	476
Max. Operating Pressure (bar)	5
Test Pressure (bar)	10
Max. Working Temperature (c)	90
Heating Elements	1 No. Incoloy Immersion
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Heat Loss (W)	102
Heat up Time (mins)	42
Boiler Coil Surface Area (m ²)	0.77
Boiler Coil kW Rating	22
Solar Coil Surface Area (m ²)	1.15
Solar Coil kW Rating	30
Product Code	CEMVS-0400LFC
Energy Efficiency Class	C

Dimensions

A	1570
B	710
C	225
D	275
E	430
F	615
G	680
H	745
I	888
J	1130
K	1180
L	1280



Unit 17 C&D Power Road, Plantation Business Park, Bromborough, Wirral CH62 3RN, UK
 www.jouleuk.co.uk | info@jouleuk.co.uk | Phone +44 1513 551094