

300 L Direct

| | | | |
|----------|----------|--------|----------------|
| Capacity | Type | Model | Installation |
| 264L | Unvented | Direct | Floor Standing |

Descriptive Specification

- The unit is to be floor standing InterCyl pre-insulated pressurised Hot Water Cylinder.
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 52 W.

Constructive Specifications

| | |
|-------------------------------|---|
| Capacity | 264L |
| Cylinder Material | Stainless Steel Duplex LDX 2101 |
| Thermal Insulation | Polyurethane foam CFC-Free and HCFC Free |
| Casing | Painted Galvanised Carbon Steel DX51D |
| Coil Material | Stainless Steel Tube AISI 316L |
| Weight (empty) kg | 55 |
| Weight (full) kg | 319 |
| Max. Operating Pressure (bar) | 5 |
| Test Pressure (Bar) | 10 |
| Max. Working Temperature (c) | 90 |
| Heating Elements | 2. No Incoloy Immersion |
| Unvented Kit Components | Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish |
| Height (mm) | 1986 |
| Diameter (mm) | 545 |
| Standing Loss (kWh/day) | 1.81/24 hours |
| Product Code | TRIMVD-0300LFC |
| ErP Band | C |

Dimensions

| | Product | 210D |
|---|-------------|------|
| A | Cold Inlet | |
| B | Immersion 1 | |
| C | Immersion 2 | |
| D | T&P Valve | |

