

210 L Twin Coil

Capacity	Type	Model	Installation
210L	Unvented	Twin Coil	Floor Standing

Descriptive Specification

- The unit is to be floor standing InterCyl pre-insulated pressurised Hot Water Cylinder.
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 52 W.

Constructive Specifications

Capacity	210L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	48
Weight (full) kg	232
Max. Operating Pressure (bar)	5
Test Pressure (Bar)	10
Max. Working Temperature (c)	90
Heating Elements	1. No Incoloy Immersion
Unvented Kit Components	Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Height (mm)	1511
Diameter (mm)	545
Standing Loss (kWh/day)	1.40
Product Code	
ErP Band	B

Dimensions

	Product	210T
A	Cold Inlet	190
B	Bottom Coil	338
C	Top Coil	688
D	Immersion	738
E	Secondary Return	882
F	T&P Valve	982

