

## 96 L Direct

| Capacity | Type   | Model  | Installation   |
|----------|--------|--------|----------------|
| 96L      | Vented | Direct | Floor Standing |

### Descriptive Specification

- 900 x 400 open vented copper indirect double feed coil type cylinder pre-insulated

### Constructive Specifications

|                                |                                    |
|--------------------------------|------------------------------------|
| Cylinder Dimensions            | 900mm X 400mm excluding insulation |
| Mounting                       | Vertical floor standing            |
| Capacity                       | 96 litre                           |
| Cylinder Body Material         | Copper                             |
| Connections Material           | Copper                             |
| Heat Exchanger Material        | Copper                             |
| Max Working Head               | 10 metre                           |
| Max Length of Immersion Heater | Top Entry 700mm                    |
| Coil Rating                    |                                    |
| Max Primary Pressure           | 3.5 BAR                            |
| Insulation                     | Polyurethane Spray                 |
| Declared Heat Loss             | 1.49 KWH/24H                       |
| Declared Heat Loss             | 62 WATTS                           |
| Energy Efficiency Band         | C                                  |
| Product Code                   |                                    |



### Dimensions

|   | Product        | 96L |
|---|----------------|-----|
| A | Cold Feed      | 100 |
| B | Primary Return | 100 |
| C | Primary Flow   | 695 |