

## RM Cylinders ERP Data Stelflow Slimline Direct Electric WaterHeaters

Manufacturer	Model	Type	Production Code	Capacity	Standing Heat Loss of Vessel	Standing Heat Loss of Vessel	ERP Energy Banding	ERP Tapping Profile	Temperature Set	ERP Energy Efficiency	Daily Energy Usage Qelec	Yearly Energy Usage AFC	Yearly Energy Usage AEC	Off Peak Usage	Noise Level
				Litre	KWH/24H	Watts	A-G		°C	ηwh (%)	kWH/Day	kWH/Year	GJ/Year	Yes/No	DB
RM Cylinders	Stelflow	Direct Slim	S60DS	90	0.92	38	C	M	60	37	7.251	1592	6	No	15
RM Cylinders	Stelflow	Direct Slim	S90DS	120	1.03	43	C	M	60	36	7.110	1561	6	No	15
RM Cylinders	Stelflow	Direct Slim	S120DS	150	1.24	52	C	M	60	34	7.085	1493	5	No	15
RM Cylinders	Stelflow	Direct Slim	S150DS	180	1.44	60	C	M	60	34	7.285	1527	5	No	15
RM Cylinders	Stelflow	Direct Slim	S180DS	210	1.53	64	C	L	60	37	13.985	3071	11	No	15
RM Cylinders	Stelflow	Direct Slim	S210DS	250	1.62	68	C	L	60	37	13.970	3068	11	No	15