

## 150 L Twin Coil

Capacity	Type	Model	Installation
150L	Unvented	Indirect	Floor Standing

### Descriptive Specification

- The unit is to be floor standing Stelflow pre-insulated pressurised Hot Water Cylinder.
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 52 W.

Constructive Specifications	
Capacity	150L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	34
Weight (full) kg	181
Max. Operating Pressure (bar)	5
Test Pressure (Bar)	10
Max. Working Temperature (c)	90
Heating Elements	1. No Incoloy Immersion
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Height (mm)	1100
Diameter (mm)	545
Immersion Reheat (mins)	57
Indirect Reheat (mins)	17
Standing Loss (kWh/day)	1.41
Heat Exchanger (kw)	16.46
Solar Volume (L)	77
Product Code	TRSMVS0150LFC
ErP Band	B

### Dimensions

	Product	150T
A	Cold Inlet	195
B	Solar Return	310
C	Solar Flow	310
D	Stat Pocket	365
E	Boiler Return	660
F	Boiler Flow	660
G	Stat Pocket	765
H	Second Return	-
I	Immersion	
J	T&P Valve	900

